

What is claimed is:

1. A flashlight apparatus comprising: a base member; a light emitting member; and a support member; the base member, the light emitting member, and the support member being pivotally connected to one another.
2. The flashlight apparatus of claim 1, wherein the base member includes a pocket-sized multi-function tool.
3. The flashlight apparatus of claim 2, wherein the support member is pivotally mounted to the utility tool.
4. The flashlight apparatus of claim 3, wherein the base member and the light emitting member are disposed in end to end relation and pivotally mounted to one another.
5. The flashlight apparatus of claim 3, wherein the support member includes a pair of wire leg portions.
6. The flashlight apparatus of claim 1, wherein the light emitting member includes a light source, a power source connected to the light source, and a housing for containing the light source and the power source.
7. The flashlight apparatus of claim 6, wherein the housing of the light emitting member includes a space for an auxiliary power source.
8. The flashlight apparatus of claim 1, wherein the support member includes a plurality of support segments pivotally connected to the base member.
9. A flashlight apparatus comprising:

a base member, a light emitting member disposed in end-to-end relation with the base member and pivotally connected to the base member, and a support member pivotally connected to the base member.

10. The flashlight apparatus of claim 9, wherein the base member includes a pocket-sized multi-function tool.

11. The flashlight apparatus of claim 10, wherein the support member includes a pair of wire leg portions.

12. The flashlight apparatus of claim 9, wherein the light emitting member includes a light source, a power source connected to the light source, and a housing for containing the light source and the power source.

13. The flashlight apparatus of claim 12, wherein the housing of the light emitting member includes a space for an auxiliary power source.

14. The flashlight apparatus of claim 9, wherein the support member includes a plurality of support segments pivotally connected to the base member.